

## January/February 2010

www.sbcmag.info



PLUS: Pulley Use in SBCRI Softwood Lumber Supply

CHANGE SERVICE REQUESTED



РRSRT STD U.S. Postage Madison, WI Permit No. 2223

SBC Magazine • 6300 Enterprise Lane • Suite 200 • Madison, WI 53719

## NOW MORE THAN EVER YOUR SUCCESS IS OUR SUCCESS.



From software to equipment, MiTek is dedicated to helping our customers succeed. Here's what a few of them have to say about how working with MiTek has helped their businesses:

#### **SHOPNET**®



"The thing we like the most about ShopNet<sup>®</sup> was moving from stacks and stacks of paper to nothing — no paper at all. In the past, if I had to change an opening in a panel

I had to pull all the paperwork from the shop floor, change the opening, resubmit the drawing, insert it in the stack of paper and take it back to the floor. I actually had to shut down production to make the change in the opening. Now I just make the change in ShopNet and it is seamlessly inserted into the production for the day. No shutting down of the line."

Shane Morris – Designer/IT HD Building Systems, Franklin, Indiana

#### **MBA**<sup>®</sup>



"Overall MBA® has been very well accepted by everyone here. It is a core application, and we would not consider running the business without it. As the business

has grown, we have moved to electronic storage of our information and MBA has played a large part in making this possible. We use Lean Manufacturing not only in our plant but also in our offices, and MBA has helped us by centralizing our information."

Mike Boulet – Owner Mainely Trusses, Fairfield, Maine

FOR MORE SUCCESS STORIES VISIT WWW.MII.COM/YOURSUCCESS

"I was amazed at the way ShopNet performed just the way it was supposed to. This is very unusual for a piece of software. We did a time study and we saw a 30% increase in productivity. I'd like to keep ShopNet® a secret!"

> Shane Morris – Designer/IT HD Building Systems, Franklin, Indiana

#### VIRTEK<sup>®</sup> LASER PROJECTION



"We were amazed at how easy the MiTek software tied into the Virtek laser projection system. The lasers, along with the MiTek software, helped

improve the productivity on our shop floor.

I love their customer service - if we have a problem, we call up MiTek and it is taken care of."

Mike Kaufman — Manager Truss Systems, Sunnyside, WA

#### **PLANX<sup>™</sup> RETROFIT**



"MiTek presented multiple options and we worked directly with their customer service department to arrive at a system that suited us. The customer

service technicians were very knowledgeable and the system has worked far better than we ever expected. I would say we average at least triple the board foot production per man-hour with the PLANX system.

I would definitely recommend the PLANX system to other component manufacturers."

Tom Lambertz - Director of Truss Operations Roberts & Dybdahl, Des Moines, IA



The very best support to get your equipment purchase up, running and productive. www.mii.com/mitekassurance

SOFTWARE EQUIPMENT **CONNECTOR & BRACING PRODUCTS** ENGINEERING SERVICES



# Our Valued Supporters...

These companies provide significant sponsorship of the structural building components industry.



## Many thanks for their ongoing support!

For more information about our 2010 Program Advertisers or advertising in general, visit the SBC website at www.sbcmag.info or call 608/310-6706.



## GoldAdvertisers

BCMC\* Clark Industries\* (p. 19) Eagle Metal Products\* (p. 15) ITW Building Components Group\* (p. 8, 23) Lakeside Trailer Manufacturing\* (p. 22) Masengill Machinery Co. (p. 8) MiTek Industries, Inc.\* (p. 2-3) Panels Plus\* (p. 11) Qualtim, Inc.\* (p. 18) SBCA\* (p. 24) Simpson Strong-Tie Co.\* (p. 14) Southern Pine Council\* (p. 19) Viking – Wall Panel Systems\* (p. 13) Wood Truss Systems, Inc.\* (p. 22)

\*Indicates Charter Advertiser Status Listing based on contracts received as of 12/15/09

**Silver**Advertisers

Pennsylvania Lumbermens

BronzeAdvertisers

Stiles Machinery, Inc. (p. 17)

Wasserman & Associates, Inc. (p. 15)

Mutual Insurance Co. (p. 15)

Finnforest USA\* (p. 14)

Eide (p. 6)

# STRUCTURAL BUILDING HE FUTURE OF FRAMINC

Publisher Truss Publications, Inc. 6300 Enterprise Lane • Suite 200 Madison. WI 53719 Phone: 608/310-6706 • Fax: 608/271-7006 trusspubs@sbcmag.info • www.sbcmag.info

Editor Steven Spradlin Capital Structures Inc. • sspradlin@sbcmag.info

Art Director Melinda Caldwell 608/310-6729 • mcaldwell@sbcmag.info

Managing Editor & Circulation Director Libby Maurer 608/310-6724 • Imaurer@sbcmag.info

Editorial Assistant & Staff Writer Emmy Thorson-Hanson 608/310-6702 • ethorson-hanson@sbcmag.info

**Editorial Review** Suzi Grundahl 608/310-6710 • sgrundahl@sbcmag.info

Advertising Sales & Marketing Peggy Pichette 608/310-6723 • ppichette@sbcmag.info

Jan Pauli 608/310-6746 • jpauli@sbcmag.info

Kirk Grundahl 608/274-2345 • kgrundahl@sbcmag.info

Staff Writers for January/February Rvan J. Dexter. P.E.

Accountant Mike Younglove 608/310-6714 • myounglove@sbcmag.info

**Computer Systems Administrator Rick Saindon** 608/310-6717 • rsaindon@sbcmag.info

Send all ad materials, insertion orders, contracts & payments to: Truss Publications, Inc. 6300 Enterprise Lane • Suite 200 Madison, WI 53719 Phone: 608/310-6706 • Fax: 608/271-7006 trusspubs@sbcmag.info • www.sbcmag.info

The mission of Structural Building Components Magazine (SBC) is to increase the knowledge of and to promote the common interests of those engaged in manufacturing and distributing structural building components. Further, SBC strives to ensure growth, continuity and increased professionalism in our industry, and to be the information conduit by staying abreast of leading-edge issues. SBC's editorial focus is geared toward the entire structural building component industry, which includes the membership of the Structural Building Components Association (SBCA). The opinions expressed in SBC are those of the authors and those quoted, and are not necessarily the opinions of Truss Publications or SBCA



Page 16



Page 20 Lumber Supply



Jan/Feb 2010

www.sbcmag.info

## contents

by Steve Kennedy



**Pulleys Used to Ensure Known Applied Load** & Even Load Distribution by SBCRI staff

#### The Future of the Softwood by Libby Maurer & Kirk Grundahl

Editor's Message **Technical Q&A Parting Shots** 

7 10 22

Copyright ©2010 by Truss Publications, Inc. All rights reserved.

## What do all these tables have in common?



Old technology turned state-of-the-art withWizardPDS<sup>®</sup> drop-in ChannelS<sup>™</sup> Your table + our technology = ZERO Set up time and NO manual jigging.



We bring the best together! Toll free 800-344-3433 Ph. 612-521-9193 Fax 612-521-9307 www.eideintegratedsystems.com Eide Integrated Systems, LLC PO Box 11397 / 3219 North Second Street Minneapolis, MN 55411-0397

For reader service, go to www.sbcmag.info/eide.htm



Tales of Living in the Stick Frame Zone of America

What to unlearn and learn to succeed in the wall panel business

live in an area of the country that is mostly stick framed. We always seem to run into issues with framers. They want the same amount of money to stick frame a roof as they want to set trusses. We felt like the only way to make any headway into our market was to offer the labor on the jobs and become the framer. The best method to solve our issues was to offer the complete frame package including labor. Of course, being in the manufacturing business led us to the conclusion that we should build wall panels.

This type of business model is not for everyone though. The market for wall panels can be large, but it is hard to convert. It is a completely different business that requires component manufacturers to unlearn some things and to learn a large amount of new things. Since we've been through the "unlearning" process already, I thought I'd offer tips for those of you who are thinking about doing wall panels.

#### 1. Go, See, Talk

The first thing I did was research. I even traveled to several panel plants outside of my market to see what they were doing and what they had to say. I strongly recommend this because it can give you some affordable common sense advice. It can also save you from wasting time on mistakes early on...lessons that can be very costly when you're starting up. In your quest, you may learn things you don't want to do. I learned it would be best for us to start a small, simple operation instead of aspiring immediately to a huge operation with all the bells and whistles.

#### 2. Lock Up Your Checkbook

One of my favorite pieces of advice is this: When a component manufacturer gets into the panel business he needs to lock his checkbook up. In my area, stick framing prices run from \$1.35 to \$2.25/sq ft on a simple house. It is hard to sell panels when site labor is this cheap. Plant labor for panels runs \$0.25 to \$0.35 per sq ft (rough guess). You cannot afford to tack on the dreaded overhead to this cost of labor. If you invest in equipment and buildings you have to save the money on the labor to pay for it. We can only sell panels for 25 cents per sq ft on a good day. Hence my suggestion to put the checkbook on lockdown. But here's the way I look at it. We can build panels for little or no margin and convert stick framed roofs to trusses. Most of us know how to make money on trusses. If you get people buying the complete package, there are opportunities for profit.

#### **3. Keeping Plant Operations Simple**

Today's advances in wall panel equipment are huge! The saws cut and lay out plates while optimizing waste at a very high production rate. Panel lines are built to accommodate these higher production rates. They are something to behold. But when we started, we built panels on top of wood tables with hand held nail guns until we couldn't make enough to keep up with demand. Then we built another wood table to double our production. For saw equipment we started with a \$700 compound miter pull saw. We replace it about once a year. Our set-up isn't fancy, but it works for us!

#### 4. To Sheath or Not to Sheath?

Sheathing wall panels? In my area it is worth \$.10 per sq ft if you can get it out of the framer. This amounts to around \$0.80/linear foot on an 8' tall wall. Sheathing Continued on page 8

ing curve.

at a glance

□ The wall panel business is completely

Before you start a panel operation, talk to

for stick framed walls in your market to

panel manufacturers for specific tips. □ Make sure you compare the cost of labor

your own labor and overhead costs.

different than trusses and has a learn-



#### by Steven Spradlin



info@masengills.com

www.masengills.com

For reader service, go to www.sbcmag.info/masengill.htm

**Editor's Message** Continued from page 7

walls in your plant cuts production capacity in half or doubles your labor costs, however you choose to look at it. If the framer can do it for less than we can (labor, overhead, profit), then I say by all means knock yourself out! You may have already guessed that we don't sheath walls in our plant. The panels are lighter and easier to handle, and just in case things aren't perfect they are easier to modify on site if they aren't sheathed

But every market is different so keep your options open. Unsheathed walls can cause some shipping issues with roller trailers with its uneven surface or a supporting surface at 3' on center. It also takes longer to plumb and line a building if the panels are not sheathed.

Good luck if you are attempting to get a wall panel business off the ground. Even after six years building walls, framers around here still want the same amount of money to frame a job with or without panels. Ah, the joys of living in the stick frame zone of America. **SBC** 

SBC Magazine encourages the participation of its readers in developing content for future issues. Do you have an article idea for a future issue or a topic that you would like to see covered? Email your thoughts and ideas to editor@sbcmag.info.

# **The Total Wall Panel Solution**







to the factory.

Intelligent Building Systems offers everything you need to design, track and build wall panels. Our revolutionary IntelliBuild design software works hand in hand with PlantNet production software to drive IBS equipment in your plant. Communication throughout the entire manufacturing process has never been easier.

to the plant manager...

#### 866-204-8046 www.intelbuildsys.com





#### **SBCA Board of Directors**

#### **Officers & Executive Committee Reps.**

- President: Steven Spradlin Capital Structures Inc. 479/725-2112 • sspradlin@capstructures.com
- President Elect/Treasurer: Joseph D. Hikel Shelter Systems Limited 410/876-3900 • joeh@sheltersystems.com
- · Secretary: Steven L. Stroder · ProBuild 303/262-8500 • steve.stroder@probuild.com
- Past President: Ben Hershey Alliance TruTrus, LLC 602/252-1772 • bhershev@trutrus.com
- Kenneth M. Clovd California Truss Co 951/657-7491 • kenc@caltruss.com
- Dwight Hikel
  Shelter Systems Limited 410/876-3900 • dwight@sheltersystems.com
- Frank B. Klinger South Texas Truss Co. LLC 956/982-0744 • lftcfbk@aol.com
- Joe M. Odgers Superior Steel Components, Inc. 205/230-7027

#### At-Large Representatives

- Allen Erickson Cal-Asia Truss 925/680-7701
- Greg Griggs Stock Building Supply 919/431-1000
- David Horne Universal Forest Products, Inc. 336/226-9356

#### **Directors Representing Chapters**

- Phil Adams Northwest Building Components, Inc. 208/687-9490
- Keith Azlin U.S. Components, LLC 520/882-3709
- Clyde R. Bartlett Bluegrass Truss Company 859/255-2481 · Jimmy Broach, P.E. · Atlantic Building Components & Services, Inc., · 843/565-3999
- Rick Cashman Florida Forest Products 727/585-2067
- Mark A. Casp ProBuild East 352/343-0680
- David A. Denoncourt Beau-Trusses 603/796-6200
- Jack Dermer American Truss Systems. Inc. 281/442-4584
- Barry E. Dixon True House, Inc. 904/757-7500
- James C. Finkenhoefer Truss Systems, Inc. 770/787-8715
- John Hogan Vivco Components 816/449-2161
- Lee Howe ProBuild West 503/357-2178
- Steven M. Johnson Nelson Truss. Inc. 608/884-6141
- Michael Karceski Atlas Components, Inc. 815/332-4904
- Taft Ketchum PDJ Components, Inc. 845/469-9191
- Jesse Lohse Rocky Mountain Truss Co. 406/777-0210
- Glenn McClendon Sun State Components of Nevada, Inc. 702/657-1889
- David Motter, P.E. 425/486-6466 • Richard P. Parrino • Plum Building Systems, LLC • 515/327-0698
- Michael L. Ruede A-1 Boof Trusses 772/409-1010
- Gary Sartor Stone Truss Company, Inc. 760/967-6171
- Scott Ward Southern Components, Inc. 318/687-3330
- Stephen Yoder Stark Truss Co., Inc. 330/478-2100

#### **Associate Member Directors**

- Thomas E Whatley, II Fagle Metal Products 972/350-9807
- Steve Harms iLevel by Weyerhaeuser 253/924-2700
- Keith Lindemulder
  Nuconsteel Corporation
  940/383-0593
- Stanley K. Sias Simpson Strong-Tie. Co. 925/560-9000
- Chad Ward Temple-Inland Forest Products 936/829-5511



## **New Wall Panel** Products from SBCA

Two new products from SBCA's Cold-Formed Steel Council (CFSC) feature wall panel safety tips for installation. Both products can be ordered at www.sbc industry.com/pubs.



Wall Panel and Hoisting Strap Inspection and Use Requirements applies to wood and cold-formed steel wall hoisting practices. The document encourages the use of straps when lifting panels by crane.

Guide for Handling & Installing Cold-Formed Steel Wall Panels depicts guidelines for safe installation of steel panels. It contains step-by-step storage, handling, installation, loading and altering procedures. Its colorful pictures and graphics show how to handle the panels safely. Translated in English and Spanish, it comes in an 11x17 folded or flat sheet with a blank back side. SBC

#### - clarification on SBCRI graphic: -

Several readers have asked about a graphic on page 21 of the November issue. The article introduced a new device, called "WB," that accurately measures web member forces in SBCRI. The last page of the article shows sample data from a test using WB, including a picture of one truss tested and the resulting reactions. The graphic and reactions represent just one truss in a system of five. While the data and reactions listed are correct, we acknowledge that taken out of context, they appear to be inaccurate. We will provide further clarification about the graphic in a follow-up article at a later date.

SK PE



## ECHNICAL Jochnical Q & A

#### Installing Insulation in Truss Fire **Endurance Assemblies**

by SBCA Staff

Rules of thumb for if and when insulation can be added in a fire-rated assembly.



Figure 1. Example of Insulation Installation while Maintaining the Minimum Tested Truss Depth above the Gypsum Board.

#### at a glance

- Gypsum board is the most critical element in the fire endurance performance of cold-formed steel and wood truss assemblies.
- □ When adding insulation to a tested assembly, plan for an equivalent or greater plenum space.

ome tested fire endurance assemblies include insulation in the assembly; others do not. The question of whether insulation can be added to a particular assembly can be tricky. Follow these tips to figure it out.

#### Question

I have been asked to add insulation in a floor-ceiling or roof-ceiling fire-rated assembly that has otherwise been tested without it. Can I do this? And why would someone want it?

#### Answer

Reasons to add insulation could be for temperature control or sound dampening. To make a rational assessment of this modification, you must look at the properties of the insulation and the impact that its placement inside the assembly will have on the fire endurance performance of the assembly.

The effect of insulation is to reduce the flow of cold air to heated spaces and vice versa. Since insulation restricts the flow of heat, its addition to a fire endurance assembly can create heat build-up problems. The insulation will retard heat movement and may also reduce the open space (i.e., plenum) that was available for heat dissipation during the original test. Because of this, it is likely that the protective gypsum layer will heat up more quickly resulting in an increased rate of hydration. This can lead to an earlier failure of the gypsum and consequent failure of the fire endurance assembly.<sup>1</sup>

The single most critical element in the fire endurance performance of cold-formed steel and wood truss assemblies is the gypsum board, but there are ways insulation may be added to assemblies without affecting the gypsum board.

Following are some observations about the problem:

- Since insulation will retard the flow of heat through it, incorporation of insulation in a rated assembly must be kept as far away from the gypsum surface as possible. This will minimize the heat build-up that causes premature hydration.
- Since the plenum cavity helps to dissipate the heat as it passes through the gypsum membrane, maintaining a plenum space that is greater than or equal to that of the tested assembly is critical to the field assembly's performance in a fire.

Therefore, to incorporate insulation into a tested assembly, an equivalent or greater plenum space should be maintained and the insulation must be placed as far away from the gypsum surface as possible (see Figure 1).

As a general rule of thumb, it is allowable to add insulation to an assembly provided that the depth of the truss is increased by the depth of the insulation and that the insulation is maintained at the maximum distance possible from the gypsum surface. **SBC** 

To pose a question for this column, call the SBCA technical department at 608/274-4849 or email technicalga@sbcmag.info

## Here's an example. -

A specific truss application calls for an 18" deep truss. A 12" deep truss assembly was tested and passes the 1-hr. fire endurance requirement, with 5/8" Type X gypsum directly attached to the bottom chord and 5/8" plywood directly attached to the top chord. The resulting plenum space for this assembly is 12". We plan to apply the rating from the 12" tested assembly to the truss with a depth of 18".

If insulation is to be added to this hypothetical 18" assembly without diminishing its fire endurance, consideration must be given to the following points:

- Pursuant to Underwriters Laboratories' Fire Resistance Directory.<sup>2</sup> increasing the depth of an assembly does not adversely affect its fire endurance rating. In fact, increasing the depth may actually enhance performance through better heat dissipation properties, and through reduced chord stresses resulting from a larger moment of inertia for the truss section.
- The addition of insulation must be kept as far away as possible from the surface of the gypsum, so that it does not speed up the hydration process unduly, and so that the additional weight of the insulation will not cause a premature collapse.

Therefore, it is logical to assume that insulation can be added to this truss fire endurance assembly since the depth of the assembly has increased to 18"; the extra 6" of space can be filled with insulation. This insulation would be attached 12" above the gypsum membrane. This maintains the original test plenum depth and is a conservative approach.

A argument could be made for the allowance of insulation within the 12" free plenum space, but this should be dealt with on a case by case basis, since the final performance of the assembly is dependant on the insulation density, the type of gypsum used, the stresses developed in the chords of the trusses, etc. It is wise to obtain professional engineering assistance in situations like this.



SBCA offers two documents that list all the fire-rated cold-formed steel and wood truss assemblies that are currently available. It should be noted that certain assemblies from Underwriters Laboratories and Gypsum Association allow the addition of any depth of insulation at any location in the tested truss assembly as long as another layer of gypsum (of the same type as specified in the tested assembly) is installed at the ceiling.

<sup>1</sup> Metal Plate Connected Wood Truss Handbook, 3rd Edition, Section 17: Fire Performance of Trusses, www.sbcindustry.com/fire.php

<sup>2</sup> 2009 UL Fire Resistance Directory: General information on fire resistance ratings (BXRH)

## Wall Panel Opportunities Come In Many Sizes.

Whatever your opportunity, we can custom-build the equipment that will help vou meet it. Whether it's a 16' sheathing station or a 70' squaring table like the one we recently shipped to a Canadian plant. Custom equipment to fit your circumstance provides manufacturing efficiencies to make your products competitive. In tight markets where you need to look at everything, the answers will be in the small details that add up to controlling your costs.

#### These machines were custom built to fit each customer's needs in their plants:



For reader service, go to www.sbcmag.info/panelsplus.htm



ver the last couple of years my company has done a lot of research on the best way to build a wall panel business. We saw an opportunity to provide another value-added product to our customers and wanted to make sure we learned as much as possible about building them. In my research, I've seen a lot of walls framed in the field. Based on what I've seen, I believe that a very high percentage of these would not pass a comprehensive code review. I am writing this article so that the same could not be said for your wall panels.

How would you answer these questions: Are you building your wall panels per the prescriptive requirements of the building code? Who in your operation is responsible for the details and what would happen if the building department red tags a wall panel as not meeting the code requirements?

The details for framing walls in the International Residential Code (IRC) are not always very clear and even when they are clear they may not be followed. One needs to be cautious when detailing wall panels to ensure they meet not only the requirements of the customer but also the building code.

#### **Common Questions**

Here are five specific panel manufacturing items that are commonly skipped over or misunderstood.



- 1. Do you know how many jack studs are required under a 6' window header on an exterior wall or how many full (king) studs are needed?
- 2. What about nailing? What on-center spacing is required if it's part of the braced wall line?
- 3. Do you know if that particular wall is part of the braced wall line?
- 4. Let's say the plans call out the braced wall lines or shear walls and specify 2" on center for the edge and 12" in the field using 10d nails. Do the nails your company uses in walls meet this? What is a 10d nail today?
- 5. How many studs should be placed under your girder trusses, and if this is questioned do you have backup information to provide to the building department?

This article will point you in the right direction on some of these questions to help keep you building to code.

You should already have a copy of the IRC or local codes and the Wood Frame Construction Manual (WFCM) in your reference library, especially if you're building walls. The IRC prescriptive requirements for wall framing have been a subject of intense scrutiny and revision since the 2003 version of the IRC. The 2009 version is by far the

> best version to date, so it is worthwhile to get a copy (as well as the one your local jurisdiction is using). The WFCM is a referenced standard in IRC and has much more detail as well as tables to make your job easier. You can get these through International Code Council's (ICC) and American Wood Council's (AWC) websites.

#### **Jack studs**

Jack studs are installed to support the gravity loads carried by the header. The number of jack studs required can be found in IRC-06 Table R502.5(1) (see Table 1) or a similar table can be found in the WFCM table 3.22F. I suggest reviewing these tables and possibly making a more specific table with criteria that fits your area to make it easier for the technicians in your department.

			NONBEARING WALLS					
STUD SIZE (inches)	Laterally unsupported stud height <sup>a</sup> (feet)	Maximum spacing when supporting roof and ceiling only (inches)	Maximum spacing when supporting one floor, roof and ceiling (inches)	Maximum spacing when supporting two floors, roof and ceiling (inches)	Maximum spacing when supporting one floor only (inches)	Laterally unsupported stud height <sup>a</sup> (feet)	Maximum spacing (inches)	
$2 \times 3^{b}$	_	_	_	_	_	10	16	
$2 \times 4$	10	24	16	_	24	14	24	
$3 \times 4$	10	24	24	16	24	14	24	
$2 \times 5$	10	24	24	_	24	16	24	
2×6	10	24	24	16	24	20	24	

a. Listed heights are distances between points of lateral support placed perpendicular to the plane of the wall. Increases in unsupported height are permitted where ustified by analysis. b. Shall not be used in exterior walls.

Table 2. Full view of Table R602.3(5) SIZE. HEIGHT AND SPACING OF WOOD STUDS<sup>a</sup>

#### **2**King studs

King studs are installed to provide resistance to positive and negative wind pressure loads applied to the area of wall in which the opening (e.g., window or door) is located. The number of king studs that should be installed, however, is not as clear. Table R602.3(5) in the IRC says max spacing of studs is 24" on center. You'll need to extrapolate this; that is, take the number of full height studs that would have been placed within the area of the wall where the opening occurs and move them to each side. The WFCM Table 3.23C does this for you and takes advantage of the header location which may reduce the number of full-height studs required. (See Table 2 above.)

#### Braced walls

The braced wall requirements of the IRC have undergone





TABLE R502.5(1) GIRDER SPANS' AND HEADER SPANS' FOR EXTERIOR BEARING WALLS um spans for Douglas fir-larch, hem-fir, southern pine and spruce-pine-fir<sup>b</sup> and

		req	uired	numbe	∋rofj	ack st	uds)						
									GROU	JND SNC	W LO	AD (psf)	,
		30					50						
		Building width <sup>c</sup> (feet)										feet)	
HEADERS	SIZE	20		28		36		20		28		36	
SUPPORTING		Span	NJ <sup>d</sup>	Span	NJ <sup>d</sup>	Span	NJ <sup>d</sup>	Span	NJ₫	Span	NJ <sup>d</sup>	Span	Γ
	2-2×4	3-6	1	3-2	1	2-10	1	3-2	1	2-9	1	2-6	Ī
	2-2×6	5-5	1	4-8	1	4-2	1	4-8	1	4-1	1	3-8	1
	2-2×8	6-10	1	5-11	2	5-4	2	5-11	2	5-2	2	4-7	
	2-2×10	8-5	2	7-3	2	6-6	2	7-3	2	6-3	2	5-7	
	2-2×12	9-9	2	8-5	2	7-6	2	8-5	2	7-3	2	6-6	
Roof and ceiling	3-2×8	8-4	1	7-5	1	6-8	1	7-5	1	6-5	2	5-9	
	3-2×10	10-6	1	9-1	2	8-2	2	9-1	2	7-10	2	7-0	1
	3-2×12	12-2	2	10-7	2	9-5	2	10-7	2	9-2	2	8-2	1
	4-2×8	9-2	1	8-4	1	7-8	1	8-4	1	7-5	1	6-8	1
	4-2×10	11-8	1	10-6	1	9-5	2	10-6	1	9-1	2	8-2	1
	4-2×12	14-1	1	12-2	2	10-11	2	12-2	2	10-7	2	9-5	1
				-				-		-	-		4

Table 1. Partial view of Table R502.5. For the full table as well as WFCM table 3.22F, go to the Support Docs for this issue at www.sbcmag.info.

lots of changes over the past several code cycles and building departments are starting to take note. If you're in an area that does not enforce these requirements, it's only a matter of time until they will. You should become familiar with the requirements of IRC section R602.10 along with the connection tables R602.3(1)and make sure your panels are in conformance. Since we typically cannot change wall lengths or window loca-

tions you should at least look out for where you're splicing the sheathing and the nailing requirements along with any blocking requirements. View www.sbcindustry.com/wallpanels.php for more information and resources about braced wall panels. Continued on page 14

#### **ICC Revisiting Braced Wall Requirements**

This provision in the IRC may soon be changed in a way favorable to component manufacturers. At the ICC Code Hearings in October, a provision was approved to allow the vertical sheathing joints within a braced wall panel to occur at the joint between two adjacent studs. (The current requirement is that the joints must occur over a common stud.) The ICC will vote on this provision at its upcoming Final Action Hearings in May 2010. Be sure to stay on top of these changes so that when they do adopt them you know what is required.



For reader service, go to www.sbcmaq.info/finnforest.htm

#### **Building Wall Panels...** Continued from page 13

#### All 10d nails are not created equal

The 2005 National Design Specification<sup>®</sup> for Wood Construction (NDS), another great reference book that you should have (can be purchased through the SBCA website at www. sbcindustry.com/pubs), shows three nails classified as 10d: a common 0.148" diameter by 3" long, a box 0.128" x 3", and a sinker 0.120" x 2.875". If the print does not specifically call out the diameter and lengths you will need to verify which nail is needed. It's also a good idea to have conversion options ready for the nails your guns will shoot. You will also want to make sure the nails you are using, if not specified, meet the minimum code requirements.

#### **Critical Studs**

The number of critical studs that should be under a girder truss or other point loads is a column design issue that is best answered by an engineer along with most of the questions above. One prescriptive method that is commonly used is to determine the column size (i.e., number of studs) based on the crushing of the plate material. You would take the total load of the girder or beam and divide it by the Fc-perp of the plate material (335 psi for SPF-south is often used for conservatism). Note that you need to check the bottom plate and the second top plate if they are different species. This calculation will give you the square inches of studs that are required to pre-



#### That's why we redesigned our new SPHR stud-to-plate connector to fit over the 1/2" sheathing typically used on pre-manufactured walls. Now you can get a high-capacity connector for high wind areas that can be installed in the factory or on the jobsite after the sheathing is on the wall. Installation and inspection are easier and the risk of damaging a hidden strap with sheathing nails is eliminated. And the SPHR is available for 4" or 6" wide walls and offers tested performance without nailing into the sill plate. Check out the latest from Simpson Strong-Tie, because our products work where you do

For more information, visit www.strongtie.com or call (800) 999-5099.

For reader service, go to www.sbcmag.info/simpson.htm







#### PENNSYLVANIA LUMBERMENS MUTUAL INSURANCE COMPANY

#### We've been protecting businesses like yours for over 100 years and we're still growing strong.

At PLM, we understand that you need an insurance company with property and casualty insurance products and services that you can trust.

For over 100 years, our experts have been providing quality claims and risk management services to the lumber, woodworking and building material industries. Remember, "you get what you pay for." We understand wood. We know your business... because it's our business too.

If you're looking for quality and value from your insurance provider, please contact the PLM Marketing Department at 800.752.1895 or log onto www.plmins.com.

Yesterday, Today, Tomorrow... grow knowing you're covered

John Smith John K. Smith, CPCU President and Chief Executive Officer

Pennsylvania Lumbermens Mutual Insurance Company One Commerce Square 2005 Market Street, Suite 1200 Philadelphia, PA 19103

SERVING CONTINENTAL UNITED STATES

For reader service, go to www.sbcmag.info/pmlins.htm

vent the plate material from being crushed. Keep in mind that you cannot adjust the Fc-perp for duration of load or repetitive member bending. This prescriptive method also assumes that the built-up column is installed to support gravity loads only and that lateral loads applied to the surface of the wall are resisted by the standard full-height wall studs at the specified on-center spacing.

Staying informed will allow this fairly complex set of information to become less complicated. It will ensure that you take full advantage of today's code requirements, add value to your wall panel products, and assure you are in compliance with the IRC requirements. **SBC** 

Steve Kennedy has over twenty years of experience in the metal plate connected wood truss industry. He has worked for several component manufacturers and plate suppliers. Steve has volunteered on numerous SBCA committees. While studying to earn his engineering degree and the University of Wisconsin, he worked closely with Professor Steve Cramer on truss related research projects.





#### **Pulleys Used to Ensure Known Applied Load** & Even Load Distribution

by SBCRI staff

n the November issue, we updated you on the new WB4 device in SBCRI, which is helping us evaluate and systematize BCSI temporary and permanent lateral restraint and diagonal bracing. The latest step in fine-tuning in situ truss assembly testing is ensuring that we know the load going into a given truss at a given location through a uniform distribution of applied loads. To do this, the SBCRI team turned to a very basic theoretical means of applying a uniform load across multiple trusses: the pulley.

#### **The Problem**

What's unique about SBCRI is its capacity to test full scale component assemblies. This means a given amount of force is applied to the assembly through devices called actuators, and then load cells placed at certain points in the assembly record and analyze how the trusses in the assembly react in response to those forces.

Tests performed on a five-truss assembly over the past few months made it clear that it is important to have the ability to apply load at specific points, measure what the exact applied load is at each point, and determine how that load distributes itself through web members monitored by WB4. To accomplish each of these things, the SBCRI team needed a way to apply the same load across the assembly in an accurate manner that was easy to set up. So they set out to address the challenge to ensure the most accurate load application possible. This led to the pulley load application concept.

#### The Approach

The team first researched previous truss tests that found a solution to the challenge at hand. A thesis written by University of British Columbia PhD student Xiaobin Song<sup>1</sup> addressed this very topic. The paper demonstrates tests on a single roof truss and a truss assembly (containing five trusses—similar to the assembly in SBCRI) that employed a system of pulleys to evenly distribute loads throughout the truss(es).

SBCRI staff adopted Song's pulley approach for its system of trusses. They installed a pulley system by running cable between pulleys straddling each truss in the system (photos 1 and 2). The load was applied from one side of the system (photo 1).

According to the pulley theory, with one end of the cable solidly affixed to a bearing point and the cable wrapped around two pulleys, the total load going into the system (the tension on the cable (P)) should have been twice the load being applied by the





Photo 2.

actuator (see Illustration 1 in sidebar). Four identical pulley systems were installed at joints J2, J4, J6 and J8, and load was applied at all four locations.

#### Flaws in the Theory

The first tests using the pulley fixture yielded unexpected results; they revealed a flaw in the theory Song had applied. The pulley arrangement did not allow the load to distribute evenly as the theory suggests. The friction in the cable-pulley system was too great. The tests indicated that the tension on the cable (P) was only 1.5 times the load exerted by the actuator onto the roof system. According to the theory (see inset), the cable's tension should have been twice the load applied by the actuator. After investigating the setup and test results, the team realized that the load distribution resulting from

Continued on page 18

<sup>1</sup> Stability and Reliability Analysis of Metal Plate Connected Wood Trusses Assemblies, Xiaobin Song, Faculty of Graduate Studies (Forestry), University of British Columbia, Vancouver, March 2009

## **How Do Pulleys Work?**



According to basic pulley statics theory, with a simple fixed pulley (illustration 1) the tension on the rope (P) is equal to the weight of the object (W). By adding the movable pulley to the fixture (illustration 2), the tension (P) on the rope is reduced to one-half the weight. Theory further states that you reduce the tension on the rope by one-third by re-orienting the pulley/rope configuration (illustration 3).

## sensible

When you invest in machinery you require a return on your investment. Weinmann automated production solutions from Stiles Machinery deliver on that return with the promise of a sensible investment. In today's market, automated solutions are providing panel and truss manufacturers the ability to remain competitive with the flexibility to grow as their business requires. Stiles and Weinmann offer the proven machinery design and implementation experience you expect from the leaders - a partnership that will quickly impact your bottom line and return on investment. Learn more about how to employ the promise of sensible automation.

#### For more information, contact Michael Miller,

Director of Building Automation, at 616.698.7500 or mmiller@stilesmachinery.com or visit www.stilesmachinery.com.





For reader service, go to www.sbcmag.info/stiles.htm

Photo 1

#### **CNC Linear Saws**

- Five-axis machines • 7/8" x 2" - 6 7/8" x 16 1/2" cross section
- EWP materials to 60'
- Cut, mark and layout abilities
- Route, drill and milling functions • One operator

#### Robotic Material Handling

- Most efficient in the industry Increase machine availability and operator output
- · Automatically access 5-12 full bunks of raw materials
- · Vacuum technology

#### Wall Panel Automation

- Reduces labor 75%
- Computer controlled consistency
- Entry level through full automation
- · Modular and upgradable
- Framing, nail, screw, route and stacking solutions

#### **Stiles Software**

- Manufacturing Execution System (MES)
- AVIA Projection System
- Custom Applications







Photo 4



Photo 5.



It's a new year and it's time for a new look!

Update your marketing materials for 2010 with a new logo and business cards!

Call 608-310-6723 today to get started!

Cost-effective, custom solutions for your business needs.

For reader service, go to www.sbcmag.info/qualtim.htm

Starting at

\$75(



the pulley and cable set-up was not going to be theoretically uniform.

Reducing Friction. To cut down on the amount of friction between the pulleys and cable, the team reduced the number of contact points and installed a steel beam to distribute the load more evenly (photo 3). The new arrangement used a combination of fixed pulleys anchored to the floor (photo 4), and movable pulleys attached to long steel beams (photo 5).

The load or tension on the cable (P) is applied by the actuator at the upper right corner of Photo 3. The cable attached to the pulleys and steel beam is fixed at either end of the beam. Tension force is applied to both pulleys by the floor pullev attached to the cable that originates at the actuator (photo 6). Current tests are focused on evaluating this arrangement to ensure that the applied load onto each truss is accurate.

#### Why These Tests Are Significant.

Perfecting the pulley fixture is critical to the success of future industry testing in SBCRI because it allows us to apply loads with precision and know the magnitude of the load at each applied load point. With this information we now have a defined approach to knowing loads applied to specific points on individual trusses inside the assembly and are beginning to understand the load paths that take place through the overall roof system.

Additionally, the pulley approach has helped us understand the differential stiffness of each truss within the system by defining the variation in the load applied at each load point. This means we can also see how the stiffness of each truss influences load distribution through the entire assembly. This system generates data that will make modeling more accurate because we know the exact load applied at specific points on each truss member or joint, the stiffness of the assembly at those load application points, and the resulting displacements emanating from specific applied loads.

While small adjustments to the pulley fixture and load application system will be ongoing, the SBCRI team is confident that this type of fixture will ultimately be the long-term solution to accurate applied load and understanding the resulting load distribution. SBC





This image further illustrates the path of the tension placed in the steel cable. Tension, or load, enters the system from point 1, the cable then is tied off at point 2. This tension pulls on the pulley device at point 3, which in turn pulls equally on the cable affixed at points 4 and 5.

www.qualtim.com

www.sbcmag.info

For reader service, go to www.sbcmag.info/spc.htm



by Libby Maurer & Kirk Grundahl

#### What will a 2010 housing market recovery mean for softwood lumber supply?

#### -beetle resources:-

- A credible website for the latest pine beetle information in British Columbia: www.for.gov.bc.ca
- B.C.'s Mountain Pine Beetle Action Plan presents statistics and outlines plan objectives through 2010. www.for.gov. bc.ca/hfp/mountain pine beetle/actionplan/2005/
- Check out the U.S. action plan and infestation maps here: www.fs.fed.us/r2/barkbeetle/

Pew home sales are on the rise. Housing starts have begun to recover. All signs indicate that 2010 will be a year of slow growth for the housing construction industry. But talk of the ensuing recovery has many people wondering what to expect for softwood lumber supply and prices. This year, we'll examine the primary influences on the softwood lumber picture. From the Mountain Pine Beetle's damage to U.S. and Canadian forests to the industry adjusting to greater demand following a major housing slump that most of us have never experienced before; many factors contribute to what component manufacturers can expect in the next few years. Here's an overview.

#### **Factor 1: Fallout from the Pine Beetle**

The 2010 Winter Olympics aren't the only thing getting significant press in British Columbia. The Mountain Pine Beetle is a tiny insect that's made a not-so-tiny imprint on the future availability of quality softwood lumber from the region. The species, also known as the "bark beetle," is native to North America. In the past has attacked weak, older forests to make way for newer healthier trees—a good thing. Scientists believe that the outbreak of this beetle species since the 1990s is due to consistently warmer winters. In the past, below freezing temperatures would kill off the beetle in the winter. But recently, winter temperatures in Canada haven't dipped low enough to kill it. Additionally, hot and dry summers leave pine droughtstressed and more susceptible to beetle attack. As a result, the beetle continues to burrow its way into the bark of hundreds of thousands of acres of pine forests in British Columbia, Alberta and recently even further east into Saskatchewan. While burrowing through pine bark, the Mountain Pine Beetle leaves behind a blue-colored fungi stain that cuts off water and nutrient flow to the rest of the tree. If the beetle colonization isn't contained, the tree will eventually die.

What's more, the beetle has spread to the U.S. west, infecting various species in the Rocky Mountain states of Colorado, Wyoming, South Dakota and more. Although not nearly as widespread as Canada, the beetle has done enough damage-roughly 6 million acres so far-to impact more than 18 billion board feet (bbf) of American softwood lumber.

Scientists say that many of the infected logs can be salvaged, and the blue stain left behind by the beetle does not compromise its structural integrity if harvested early enough. The Canadian and U.S. governments have launched initiatives and dedicated federal resources at trying to stop the beetles' spread (e.g., a combined \$1 billion investment in the case of B.C. and the Canadian governments) using chemical treatments, burning techniques and cutting healthy trees around infested ones. One of the techniques is allowing increased harvesting of infested forests. Though some of this stock can be diverted to manufacturing bioenergy and engineered wood products, a surplus supply of logs exists which has driven prices down...for the moment. But when the supply runs out, some analysts expect prices to spike.

The cumulative area timberland affected in B.C. alone is estimated at more than 14 million hectares (or 39 million acres, about four times the size of Vancouver Island). Some experts say that the B.C. outbreaks will reduce the timber harvests by as early as this year. But the destruction to come from B.C. is expected to spike in 2014/2015,<sup>1</sup> and the impact of the timber losses are likely to be felt for several years. Stay tuned for a follow-up article with more details about the affect of the beetle on softwood lumber supply and prices. See inset for list of credible sources in Canada and the U.S.

#### **Factor 2: The Recoverv**

After several consecutive years of sliding demand, most analysts predict an increase in demand for lumber as the housing recovery beings this year. Rising housing starts, lean distribution channel inventories and government stimulus programs should kick-start lumber demand. But can production keep up?

In its 2010 forecast, the Western Wood Products Association (WWPA) predicts a mild 2010 recovery for lumber producers. "Given the unprecedented downturn, recovery for the lumber industry is unlikely to follow the same path as it has in the past," said David Jackson, WWPA economist. "The challenge for mills will be adjusting to a 'new normal' for the future." Though 2010's gradual recovery should prevent demand surges causing production and price spikes, the scenario is plausible for the 2011-2013 range.

Let's look at the numbers. WWPA estimates that a total of 31 bbf of lumber was consumed by the U.S. market in 2009. (About 7 bbf was used for new construction.) This is less than half of what was consumed in 2005 (roughly 65 bbf), an alltime high in lumber demand. For this year, WWPA predicts lumber demand to rise 11 percent to 34.5 bbf.<sup>2</sup> U.S. lumber producers have greatly curbed production as a result of declining demand. For instance, WWPA says Western lumber production in 2009

Increase your \$ales in 2010 post frame construction Totally glue laminated engineered product-NO NAILS!

decreased about 21 percent to just over 10 bbf, while Southern mills cut 2009 production to 11.6 bbf. Lumber imports from Canada and other foreign lumber suppliers have decreased more dramatically. Shipments from Canada are predicted to total 7.9 bbf in 2009, a decrease of 32 percent from 2008.

But WWPA anticipates U.S. lumber production will increase according to improving demand...at least in 2010. Mills in the West and South are expected to increase production 8 percent. Canada should regain some of the market share it lost over the past few years. Imports from Canada are expected to rise 18.8 percent in 2010 to 9.4 bbf.

With mill closures and lumber production falling off to roughly 43 bbf, the occurrence of a rapid rebound within the homebuilding sector could trigger a wood product supply shortage.<sup>3</sup> The ten million dollar question for our industry is when and how quickly we will emerge from the slump. "If it does turnaround guickly, we could be looking at a situation with [lumber] demand outpacing supply. But that's a question mark at this point," says Al Schuler, economist with the U.S. Department of Agriculture Forest Service.

We will keep a close eye on homebuilding activity and new information about lumber supply in the next eighteen months.

Factor 3: China's Affordable Housing Initiative In researching this issue, it is clear that wood fiber supply is Another factor? Enter China. That's right. In November, the going to be one of the major business issues that will affect com-B.C. forest industry and the Chinese government signed a memponent manufacturers in the near future. History has proven that orandum of understanding to use wood frame construction in if our suppliers can take advantage of the economics of supply new housing construction.<sup>4</sup> B.C. predicts that the deal will yield and demand, they will. The more knowledge that we can gather, an increase in softwood lumber exports to an estimated 4 bbf the more prepared we will be to make informed decisions. **SBC** 

<sup>1</sup> www.for.gov.bc.ca/hre/bcmpb/cumulative/Summary.htm	
---	--

<sup>2</sup> www2.wwpa.org/ABOUTWWPA/Newsroom/tabid/817/Default.aspx, Lumber Industry Sees Hopeful Signs of Slow Recovery in 2010, November 9, 2009



For reader service, go to www.sbcmag.info/timbertech.htm

by 2011. As part of an initiative to expand affordable housing options in the country's urban centers, the Chinese government has also launched a new wood frame construction building code in Shanghai. Watch for continuing developments as B.C. advances wood products trade opportunities in China, and how these transactions could affect available supply.

#### Why You Should Stay Tuned...

Throughout the year, we will cover these and other topics in SBC to lay out the facts about lumber supply as we know them. We hope these topics will provoke some thought about our industry's future issues.

- How much of the supply of beetle kill logs remains?
- How long can dead trees stand, and what happens to their structural properties as they age after dead? Harvesting beetle kill lumber and its impact on lumber properties.
- If the tree fiber is not of the quality and strength needed for solid wood uses such as in wood trusses and components. are there alternative uses?
- What will be the raw material supply impact on the SBC industry?
- Will raw material change? For instance, will we see more products made from OSB or composite fiber?

<sup>3</sup> www.woodmarkets.com/p wm2006.html <sup>4</sup> www2.news.gov.bc.ca/news\_releases\_2009-2013/2009F0R0078-000617.htm



Truss and wood component machinery experts for over 30 years. We can help you enter the component industry or refine your existing facillity with custom equipment solutions featuring:

#### New & Used

- **A** Truss Production Equipment
- ▲ Wall Panel Framing Equipment Automatic & Manual Cutting Equipment:
- Component, Radial Arm, Linear Single **Blade Saws**
- A Plant Layouts / Production Consultants
- Automated Jigging Systems
- **Automated Mesuring Devices**
- A Replacement Production Surfaces

Count on effective, economical and timely solutions.

www.WoodTrussSystems.com



For reader service, go to www.sbcmag.info/wts.htm.



For over 20 years, Lakeside Trailer has led the way in the component trailer industry with innovative ideas to assure your delivery operations remain efficient in today's competitive market. With more than 1700 truss trailers to our credit. Lakeside has perfected ways to reduce or eliminate your transportation concerns



For reader service, go to www.sbcmag.info/lakeside.htm





When SBCA's West Florida Chapter says they have an annual tradition, they really mean it. For the past 24 years, the chapter has put on an educational event for building officials. Each fall, building officials and inspectors, plans examiners, and local architects and engineers join the chapter in a fantastic lunch and learn session. The free event includes educational seminar with CEU credit. truss testing demonstration and lunch. This year's class was the Component Technology Workshop (CTW) on Inspection of Installed Wood Trusses. However, the "fun" part was testing a truss to the limit, when the guests are asked to guess when the truss will fail.

Throughout the years, the chapter has shown what it takes to break field-repaired trusses, trusses with and without bracing, and additional demonstrations that show the strength of structural building components. The feedback from West Florida is undeniable—great job, guys! SBC



# Connections for your digital life



can take place.

By connecting all the parts, and all the players, with powerful new software tools, that easily communicate ideas up and down the value stream - ITW Building Components Group is building new ways to share knowledge, not just data!

See how ITW BCG helps you connect all the dots - from the first design step, to engineering, to fabrication and beyond!

Watch the ITW BCG presentation at www.itwbcg.com/software



For reader service, go to www.sbcmag.info/itw.htm

These days, the construction industry has never been more ready for new ways to save time and money. Seems everyone is looking for any advantage to help win more bids and insure a profit. While it is true that optimizing current systems and software will help in smaller ways, for a bigger impact we will have to expand our industry's reach. What's needed is a fresh perspective, from a company progressive enough to be involved in every major part of the construction industry - with the vision and resources to re-align existing business tools and create the missing links to tie everything together - so that a real revolution

# REACH FOR EXCELLENCE

**Take Your Plant to New Heights with SCORE** 



"In order to succeed, our customers need to know they can count on us to provide what's needed. Working with SBCA and becoming SCORE certified proves we are committed to excellence."

- Steve Kennedy, Engineer/Training Manager, Lumber Specialties

Set your company apart with SCORE's certification program that incorporates all of SBCA's education and training programs – helping you implement cost-effective industry best practices. Learn more about options and how to get started at <u>www.sbcindustry.com/score.php</u>.



### SCORE Elite

#### **ProBuild Manufacturing**

Anchorage, AK Big Lake, AK Chugiak, AK Kenai, AK Phoenix, AZ National City, CA Visalia, CA Dolores, CO Longmont, CO Lady Lake, FL Milton, FL Plant City, FL Norcross, GA www.probuild.com Pooler, GA Clackamas, OR Hawarden, IA Klamath Falls, OR New Hampton, IA Morrisville, PA Indianapolis, IN Mitchell, SD Valley Center, KS Buda, TX Dry Ridge, KY Carrollton, TX Grand Rapids, MI Mercedes, TX Wadena, MN West Point, VA Albemarle, NC Auburn, WA Albuquerque, NM Walla Walla, WA Berlin, NJ West Richland WA Kingston, NY Spokane, WA Delaware, OH De Pere, WI

#### **Shelter Systems Limited**

www.sheltersystems.com • Westminster, MD

Sun State Components of Nevada, Inc. www.sunstatenv.com • North Las Vegas, NV

### SCORE Leaders

Dakota Craft Truss www.dakotacraft.com Rapid City, SD

#### **Lumber Specialties**

www.lbrspec.com Dyersville, IA Story City, IA

#### Plum Building Systems, LLC

www.plumbuildingsystemsinc.com West Des Moines, IA

#### **SCORE** Achievers

Capital Structures www.capstructures.com Fort Smith, AR

#### Latco Structural Components

www.latcoinc.com Lincoln, AR

#### **Tri-County Truss, Inc.**

www.tricountytruss.com Burlington, WA

#### **True House, Inc.**

www.truehouse.com Jacksonville, FL

#### **Truss Craft**

www.dakotacraft.com Cheyenne, WY

#### Truss Systems, Inc.

www.trusssystemsinc.com Oxford, GA